

THERMOSCHALTER UND THERMOFÜHLER

TYPENTABELLE

Thermoschalter (Auswahl):

Schaltpunkt oben °C (+3/-2)	Schaltdifferenz unten °C (+3/-2)	K (+3/-2)	Zeichnungsnummer Type	max. zulässige Temperatur	
				dauernd	kurzzeitig
55	50	5	X8.121.02.000.1N	65	85
65	60	5	X8.121.04.000.1N	75	95
70	65	5	X8.121.05.000.1N	80	100
75	70	5	X8.121.06.000.1N	85	105
85	80	5	X8.121.08.000.1N	95	115
90	85	5	X8.121.09.000.1N	100	120
100	95	5	X8.121.11.000.1N	110	130
82	77	5	X8.121.22.000.20	90	110
92	96	4	X8.121.24.000.1N	90	110
102	97	5	X8.121.26.000.1N	110	130
50	45	5	X8.124.01.000.1F	60	80
55	50	5	X8.124.02.000.1F	65	85
65	60	5	X8.124.04.000.1F	75	95
70	65	5	X8.124.05.000.1F	80	100
75	70	5	X8.124.06.000.1F	85	105
80	75	5	X8.124.07.000.1F	90	110
85	80	5	X8.124.08.000.1F	95	115
90	85	5	X8.124.09.000.1F	100	120
95	90	5	X8.124.10.000.1F	105	125
100	95	5	X8.124.11.000.1F	110	130
105	100	5	X8.124.12.000.1F	115	130
92	87	5	X8.124.23.000.1F	100	120
55	50	5	X8.160.02.000.10	62	85
110	105	5	X8.160.13.000.1A	120	130
82	77	5	X8.160.22.000.10	90	110
45	40	5	X8.160.40.000.10	55	75
50	45	5	X8.161.01.000.10	60	80
100	95	5	X8.161.11.000.10	110	130
110	105	5	X8.161.13.000.10	120	130
120	115	5	X8.161.15.000.10	120	130
92	87	5	X8.161.23.000.10	100	120
92	96	4	X8.161.24.000.10	90	110
100	95	5	X8.165.11.000.10	110	130